PEXALCONNEX-T



Derivation clamp for multilayer systems









Connex-T: a revolution in multilayer pipes



Connex-T is truly a revolution in the installation of multilayer systems. Developed by Valsir to create derivations on new or existing multilayer pipes with large diameters, it provides significant reductions in installation time and costs and facilitates maintenance work.

The solutions adopted have been studied so that margins of error are minimised and installation is facilitated: it is not always easy to intervene on existing pipelines due to the position and the limited space in which the job needs to be performed.





The particular profile of the connection with the pipe has been designed and engineered specifically to reduce pressure loss to a minimum.

Tested in accordance with the strictest international standards on multilayer systems and subject to the most rigid quality tests in Valsir, Connex-T has a guaranteed durability of at least 50 years in full observance of the standards; in this period a use at pressures of 10 bar and at temperatures up to 95°C is allowed.

Ø Pexal pipe	Ø outlet
50	½"M
63	3∕4"M
75	3∕4"M
75	1"M
90	1"M

MADE IN ITALY



THE CHARACTERISTICS OF THE CONNEX-T CLAMP



Fast and easy installation in every situation on existing pipelines.



The screw holes have special profiles that prevent screws loosening during installation.



On existing Valsir multilayer pipes Connex-T allows a derivation to be created with a **significant reduction in costs** as far as the material used and labour costs are concerned. In conventional systems, in order to create a derivation, quite a long piece of pipe needs to be cut and 2 fittings must be inserted. Connex-T can be installed without cutting the pipe and without fittings.



The total resistance to corrosion, to construction materials and to the main chemical compounds make them suitable for various applications of an industrial kind.



Durability guaranteed for 50 years; when used at pressures of 10 bar and temperatures as high as 95°C.



Body in technopolymer with exceptional characteristics of **mechanical resistance**.



Significantly reduced pressure loss as compared with a conventional T fitting. Connex-T does not reduce the pipe bore section and the special profile of the insert minimises pressure loss.



The **blocking nut** of the threaded insert is **provided with an end-of-stroke lock system** that avoids elevated tightening forces that would damage the multilayer pipe.



Wide range of diameters from 50 mm \emptyset to 90 mm \emptyset with available derivations from $\frac{1}{2}$ " up to 1".



The clasps placed on the sides to block the two parts keep the two pieces in place during assembly and prevent them from falling during the installation phase.



The system is composed of completely non-toxic materials **certified to transport food liquids and drinking water**.



Locknuts are incorporated in the rear half-shell to simplify screws tightening.

The housing where they are inserted is designed to avoid screws loosening during installation and to guarantee a greater tightening torque.



The Connex-T system is produced with fully recyclable materials that at the end of their life cycle can be recycled.

The manufacturing processes employed are energy efficient and with a low environmental impact. Valsir has adopted the Green Building principles in the interests of environmental protection and resources conservation.



Tested according to the strictest international standards on multilayer systems (DVGW W542, DVGW W534, EN ISO 21003 -2 -3 and -5).



THE DETAILS THAT MAKE THE DIFFERENCE

A number of innovative solutions have been designed for Connex-T to reduce installation time

and eliminate margins of error in order to help the plumber that must often work in tight spaces.

Blocking nut with end-of-stroke system

The threaded insert blocking nut has been designed for an easy and safe installation. It is provided with an end-of-stroke lock system that avoids elevated tightening forces that would damage the multilayer pipe.



Blocking system of the half-shells

Special clasps placed on the half-shells allow the two parts of the Connex-T to be blocked before they are fully tightened with the screws, thus preventing the two pieces from disconnecting and falling on the ground.



Anti-loosening system of the screws

Special profiles have been created in the holes where the screws are inserted to avoid them loosening during installation. The screw head allows the use of both socket wrenches and screwdrivers for tightening.



Locknuts incorporated

Locknuts are incorporated in the rear half-shell thus guaranteeing improved screws tightening. The housing where they are inserted is designed to avoid screws loosening during installation and to guarantee a greater tightening torque.






EASY AND SAFE INSTALLATION



Step 1

Use the centring hole placed in the rear half-shell to create the guide hole (use a 6 mm \varnothing drill bit for metal).



Step 2

Create the hole through an appropriate hollow cutter using the centring hole as a guide for the cutting tip. While drilling, keep the drill perpendicular to the pipe axis.



Step 3

Remove any cutting burrs and sharp edges inside the hole using the fine sandpaper provided. Clean the hole in order to eliminate any residue on the edge and inside the hole.





Step 4

Put the threaded insert and the front half-shell inside the hole, positioning it over the pipe.

Turn the blocking nut by hand in order to secure the half-shell to the pipe.



Step 5

Place the rear half-shell and secure it to the front shell using the special fastening clasps, in this way the two parts will remain attached to the pipe. Tighten using the provided screws with a 6 mm \varnothing socket wrench or a screwdriver.



Step 6

Fully Turn the locking nut on the threaded insert until end-of-stroke.





TECHNICAL SUPPORT AND ASSISTANCE

Valsir provides complete support both during the designing phase and on site, thanks to a first class technical office made up of a team of highly experienced engineers, capable of dealing with the most complex system requirements. Valsir also boasts an important training centre called Valsir Academy catering for clients, distributors, plumbers and planners. Highly equipped halls are available where theoretical and practical courses are organized, also on the use and design of water supply systems using the Silvestro software, a software specifically developed within Valsir.





SILVESTRO SOFTWARE


The design of floor and radiator heating systems, water supply as well as waste and drainage systems, is extremely easy and the production of the project technical documents is rapid when using the Silvestro software program.

Rapid, simple, unique, Silvestro has numerous strong point:

- rapid learning curve thanks to a simple and intuitive interface;
- completely graphic background that facilitates input of the project details;
- automatic drawing of the loops in the floor radiant systems;
- automatic repositioning of the stack points on the plan view;
- generation of calculation reports that are exportable in an .xls format;
- import and export of files in .dwg format;
- immediate update of software with a guided procedure;
- creation of complete bill of materials from the project files.







QUALITY AND SUSTAINABILITY



Efficient processes and reliable products are not the only parameters used to evaluate a company conduct: today, in fact, the capacity of the company and its management team to design and implement production processes that are sustainable from an environmental point of view are of equal importance. Valsir has always been committed to the manufacture of recyclable products and the implementation of sustainable processes, in line with the most advanced Green Building principles (green building and environmentally friendly project design), and today boasts highly sustainable production plants which, thanks to the use of renewable energy and planning that aim at the conservation of resources, have obtained a Class A energy certificate.

The consistency of Valsir commitment is demonstrated by its **product approvals** which amount to **170** in total, obtained around the world from the most severe certification bodies (figure updated on 01/07/2015), and by the **certified quality system** in compliance with the European Standard **UNI EN ISO 9001:2008**.



Production processes and management systems that are verified, monitored and certified.



Sustainable production plants and processes, use of renewable energies, sustainability of resources.



Products that are verified, monitored and certified by recognized certification bodies.



Recyclable products and low impact production processes in line with the Green Building principles.



THE VALSIR RANGE























VALSIR S.p.A.

Località Merlaro, 2 25078 Vestone (BS) - Italy Tel. +39 0365 877.011 Fax +39 0365 81.268 e-mail: valsir@valsir.it

www.valsir.it















